



Time Clock - Carbon Filters Fiberglass Tank – Duplex Parallel

Features:

- Automatic time clock initiated regeneration
- Unfiltered Water bypass during regeneration
- Low lead brass valve
- Self cleaning, hydraulically balanced positive acting piston control valve
- ABS tank liners for longer service life. FRP wrapped for strength and corrosion resistance
- ANSI/NSF listed tanks
- 120V/60 Hz/ 1PH operation



C-241C-TC-D

Pipe Size	Fleck Valve Type	Model Number	Part Number	Mineral Tank Size (inches)	Media Qty. per Tank (CuFt)	Ship. Wt Lbs	LIST PRICE Call for pricing
1"	2750	C-121A-TC-D	(2) - 12000061	12"x52"	2	340	
1"		C-141A-TC-D	(2) -12000062	14"x65"	3	450	
1"		C-161A-TC-D	(2) -12000063	16"x65"	4	650	
1.5"	2850	C-141B-TC-D	(2) -12000064	14"x65"	3	480	
1.5"		C-161B-TC-D	(2) -12000065	16"x65"	4	680	
1.5"		C-201B-TC-D	(2) -12000066	20"x62"	6	820	
1.5"		C-241B-TC-D	(2) -12000067	24"x71"	10	1320	
2"	2900	C-161C-TC-D	(2) -12000068	16"x65"	4	700	
2"		C-201C-TC-D	(2) -12000069	20"x62"	6	840	
2"		C-241C-TC-D	(2) - 12000070	24"x71"	10	1340	
2"	3150	C-301C-TC-D	(2) - 12000071	30"x72"	15	1920	
2"		C-361C-TC-D	(2) -12000072	36"x72"	20	2400	
3"	3900	C-361E-TC-D	(2) -12000073	36"x72"	20	2500	
3"		C-421E-TC-D	(2) -12000206	42"x72"	30	3860	
3"		C-481E-TC-D	(2) -12000207	48"x72"	40	5220	

(LT) Liquid Treatment Technologies Standardized Products

Phone: 508-586-9972

www.lttechnologies.com



Duplex Parallel Carbon Filters

Model Number	Recommended Flow Rates ⁽²⁾				Mineral Tank Size in.	Pipe Size in.	Max. Drain Flow GPM	Carbon Media Qty. Cu. Ft.	Space Req. ⁽³⁾ LxDxH in.
	Chlorine		Organic ⁽⁴⁾						
	GPM Flow	PSI Drop	GPM Flow	PSI Drop					
C-121A	16	5	8	3	12x52	1	7	4	30x12x59
C-141A	22	6	12	3	14x65	1	10	6	34x14x71
C-161A	32	7	16	4	16x65	1	15	8	42x16x72
C-141B	22	4	12	3	14x65	1.5	10	6	34x14x71
C-161B	32	4	16	3	16x65	1.5	15	8	42x16x72
C-201B	44	6	22	3	20x62	1.5	20	12	46x20x70
C-241B	60	9	30	5	24x71	1.5	30	20	54x24x82
C-161C	32	4	16	3	16x65	2	15	8	42x16x72
C-201C	44	4	22	3	20x62	2	20	12	46x20x72
C-241C	60	5	30	3	24x71	2	30	20	54x24x87
C-301C	100	8	50	4	30x72	2	50	30	66x31x91
C-361C	140	12	70	5	36x72	2	70	40	78x37x91
C-361 E	140	5	70	3	36x72	3	70	40	78x37x96
C-421E	190	7	96	4	42x72	3	100	60	90x43x96
C-481E	250	8	126	4	48x72	3	125	80	102x49x96

NOTES:

- 1) Units provided with 7-day time clock and by-pass during reconditioning. Other controls and no water by-pass available. Consult factory.
- 2) Pressure drops are based on clean bed operation. Pressure drops and weights are estimates
- 3) Not including operating and maintenance areas.
- 4) FM-6 is provided for chlorine reduction. FM-44 is recommended for organic applications, but must be specified when ordering. Cost adders will apply

(LT) Liquid Treatment Technologies Standardized Products

Phone: 508-586-9972

www.lttechnologies.com